

**DECLARATION OF PERFORMANCE:
DoP-VWUAB-VWWI-006****Rev 4: 01/07/2020**EN 14351-
1:2006+A1:2010NorDan UAB
Montuotoju 6
LT 89101 Mazeikiai
Lithuania
info@nordan.lt

In accordance CPR (Construction Products Regulation) 305/2011, we hereby declare that the following NorDan products as shown in Table 1, being manually operated windows / doors for fitting vertically in domestic and commercial buildings and produced by:

- NorDan AS Stasjonsvein 46 N-4460 Moi. Norway
- NorDan AS Skansen, N-2670 Otta. Norway
- NorDan AS Tengsareidveien 1,N-4373 Egersund. Norway
- NorDan AB Kvadervägen 1 SE-330 15 Bor. Sweden
- NorDan AB Nyboholm SE-570 16 Kvillefors. Sweden
- NorDan AB Grebbestadsvägen 8, SE-457 91 Tanumshede. Sweden
- NorDan SP.zo.o, UL. Fabryczna 16, 64-200 Wolsztyn, Poland
- NorDan UAB, Montuotoju 6, LT-89101 Mazeikiai, Lithuania

-are in accordance with product standard EN 14351-1:2006+A1:2010, declared using system of attestation 3 in annex ZA.2 of EN 14351-1:2006+A1:2010 and verified by assessment and ITT by the following notified bodies:

- RISE Research Institutes of Sweden (nr 0402)
- British Board of Agreement (Nr. 0836)
- SINTEF Building and Infrastructure (Nr. 1071)
- KTU Institute of Architecture and Construction (nr 2018)
- Institut für Fenstertechnik e. V., Rosenheim (nr 075)

Table 1: uPVC Arcade system doors

Characteristics / Product codes	Terrace door	Entrance door	Tilt Sliding door	Folding door
	TD1-EL	ED1-EL	TSL-EL	FLD-EL
Resistance to wind load, class (EN 12210:1999)	C3	C2	C4/B4	C2/B3
Water tightness, class (EN 12208:1999)	9A	7A	9A	7A
Thermal transmittance U_w (EN ISO10077-1:2006) & EN ISO 10077-2:2012) (W/m ² K) *	* 1,3	* 1,3	* 1,2	* 1,3
Solar energy transmission % (EN 410:2011) *	* 64	* 64	* 64	* 64
Light transmission T_v % (EN 410:2011) *	* 82	* 82	* 82	* 82
Air permeability, class (EN 12207:1999)	4	3	4	3
Acoustic performance (EN ISO 140-3:1995) R_w (C;Ctr) dB	** 34,8 (-1;-3)	npd	npd	npd
Test result for the product	1000x2100	1000x2100	1912x2213	3600x2200

* Valid for DG*2 product with a glass unit 4-16W-4LowE (glass 4mm clear, warm edge spacer Chromatech ultra, glass 4mm coated in selective coating „Clima Guard Premium2“, inside filled with argon gas 90%), which has U_g value of 1,1 (W/m²K).

** Valid for TG*3 product with a glass unit 33.1LowE-12W-4-12W-33.1LowE (33.1 clear laminated glass coated in selective coating „Clima Guard Premium2“, warm edge spacer Chromatech ultra, float 4mm glass in the middle, inside filled with argon gas 90%), which has U_g value of 0,6 (W/m²K).

npd – no performance determined

-and that the products shown in table 1 conform to the essential characteristic performance indicated. This declaration of performance is issued under sole responsibility of the manufacturer.

On behalf of manufacturer signed by:

Dainius Kubilas
Product Manager
LTU Mazeikiai 02/07/2020