

DECLARATION OF PERFORMANCE: DoP-NDUAB-AL-021-EN

NorDan UAB
 Montuotoju 6
 LT 89101 Mazeikiai
 Lithuania
 info@nordan.lt

In accordance CPR (Construction Products Regulation) 305/2011, we hereby declare that the following NorDan products as shown in Table 1, being manually operated windows / doors for fitting vertically in domestic and commercial buildings and produced by:

- NorDan AS Stasjonsvein 46 N-4460 Moi. Norway
- NorDan AS. Skansen, N-2670 Otta. Norway
- NorDan AS Tengsareidveien 1,N-4373 Egersund. Norway
- NorDan AB Kvadervägen 1 SE-330 15 Bor. Sweden.
- NorDan AB Nyboholm SE-570 16 Kvillefors. Sweden.
- NorDan AB Grebbestadsvägen 8, SE-457 91 Tanumshede. Sweden
- NorDan SP.zo.o, UL. Fabryczna 16, 64-200 Wolsztyn, Poland
- NorDan UAB, Montuotoju 6, LT-89101 Mazeikiai, Lithuania

-are covered by EN 14351-1 and are in accordance with product standard EN 13830:2003, declared using system of attestation 1 in annex ZA, verified by assessment and ITT by the following notified bodies:

- RISE Research Institutes of Sweden (nr 0402)
- British Board of Agreement (Nr. 0836)
- SINTEF Building and Infrastructure (Nr. 1071)
- KTU Institute of Architecture and Construction (nr 2018)

Table 1: HelAlu Sapa 4150 Curtain wall kit

Characteristic	ACW-SFB4150	ACW-SFB4150 SX
Resistance to wind load	Designed wind load 2000 Pa	Designed wind load 2000 Pa
Resistance to own dead load	npd	npd
Impact resistance	I4/E4	I4/E4
Air permeability *)	A4	A4
Water tightness *)	R7	R7
Fire resistance	npd	npd
Reaction to fire	npd	npd
Fire propagation	npd	npd
Resistance to horizontal load	npd	npd

npd – no property determined

*) test performed by SP as accredited testing laboratory. Not required to be tested by a notified body.

-and that the products shown in table 1 conform to the essential characteristic performance indicated. This declaration of performance is issued under sole responsibility of the manufacturer.

On behalf of manufacturer signed by:

Dainius Kubilas

Chief Product Officer

LTU Mazeikiai 10/12/2020

